

Note: This datasheet may be out of date. Please download the latest datasheet of NFE61PT330B1H9# from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=NFE61PT330B1H9%23

"#" indicates a package specification code.

NFE61PT330B1H9#







< List of part numbers with package codes >

NFE61PT330B1H9B

NFE61PT330B1H9K


NFE61PT330B1H9L

Manufacturing Co., Ltd.



Appearance & Shape





: Electrode (in mm)

В

Κ

L

Packaging

Features

The chip "EMIFIL" NFE61PT is a T-type circuit EMI suppression filter.

Packaging Information

330mm Embossed Tape

180mm Embossed Tape

Specifications

Bulk(Bag)

Features

- 1. Its large rated current of 2A and low voltage drop due to small DC resistance are suitable for DC power line use.
- 2. The feedthrough capacitor realizes excellent high frequency characteristics.
- 3. The structure incorporates built-in ferrite beads which minimize resonance with surrounding circuits.
- 4. 33 to 4,700pF lineups can be used in signal lines.

Applications

Other Usage For general

1 of 3

Standard

Packing Quantity

500

8000

2500

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





NFE61PT330B1H9#

Note: This datasheet may be out of date.

Please download the latest datasheet of NFE61PT330B1H9# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFE61PT330B1H9%23

"#" indicates a package specification code.



Specifications

Shape	SMD
Size Code (in inch)	2706
Length	6.8mm
Length Tolerance	±0.5mm
Width	1.6mm
Width Tolerance	±0.3mm
Thickness	1.6mm
Thickness Tolerance	±0.3mm
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.062g
Number of Circuit	1
Rated Current	2A
Rated Voltage	50Vdc
Withstanding Voltage	125Vdc
Insulation Resistance(min.)	1000ΜΩ
Capacitance	33pF
Capacitance Tolerance	±30%
Size Code (in mm)	6816

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date. Please download the latest datasheet of NFE61PT330B1H9# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NFE61PT330B1H9%23

"#" indicates a package specification code.






NFE61PT330B1H9#



Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

